

Technical datasheet No.: **2027.7**

**Product:** POLYMAR® CRISTAL 800 FR

**Article No.:** 3028 5340

<b>Type of coating and finish</b>		
Type of coating	<b>PVC</b>	
Burning behaviour	<b>DIN 4102: B2</b>	
Total weight	<b>1000</b> g/m <sup>2</sup>	EN ISO 2286-2
Thickness	<b>0,8</b> mm	DIN EN ISO 2286-3
Cold resistance	<b>-20</b> °C	EN 1876-1
Dimensional stability at 60°C	<b>MD &lt;5 CD &lt;2</b> %	ASTM-D 1204
High Temperature	<b>+ 50</b> °C	PA 07.04 (intern)
Remarks	<b>no scrim</b>	
Tensile strength KG/cm <sup>2</sup>	<b>MD 250;CD 190</b> KG/cm <sup>2</sup>	EN ISO 527-3
Weiterreißfestigkeit KG/mm <sup>2</sup>	<b>MD15,5;CD 15,5</b> KG/mm <sup>2</sup>	EN ISO 6383-1

These indicated technical data are based on average results. Due to production procedures deviations up to -5% can occur. All technical data are in accordance with the present standard of knowledge and give product information without legal binding. All data apply to new products. Applications suggested do not release the customer to test material for its intended application.